

## DECLARATION OF PERFORMANCE

No. DOP - JUMBO C - ALTRIPLY 5x10

1. Unique identification code of the product-type:  
Commercial Plywood, pencil cedar/campnosperma/bintangor face&back, eucalyptus & poplar core

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
Plywood, 2013 and thickness 5.5/8/9/10/12/15/18/22/25X3050mmX1525mm included in the CE mark on the packaging

3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
Plywood for internal Use as Non-Structural Components, EN 636-1NS or EN 636-2NS

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
\_\_\_\_\_

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
Mr Li Zhian

6. System or systems of assessment and verification of constancy of performance of the construction products as set out in Annex V  
AVCP 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
N/A

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
N/A

9. Declared performance

Notes to the table:

1. Column 1 shall contain the list of essential characteristics as determined in the harmonised technical specifications for the intended use or uses indicated in point 3

above.

2. For each essential characteristic listed in column 1 and in compliance with the requirements of Article 6, column 2 shall contain the declared performance, expressed by level or class, or in a description, related to the corresponding essential characteristics. The letters “NPD”(No Performance Determined) shall be indicated where no performance is declared.

3. For each essential characteristic listed in column 1, column 3 shall contain:

a) dated reference of the corresponding harmonised standard and, where relevant, the reference number of the Specific or Appropriate Technical Documentation used;

Or

b) dated reference of the corresponding European Assessment Document where available and reference number of the European Technical Assessment used. Essential characteristics (see Note 1)

Essential characteristics	Performance	Harmonised technical specification
(see Note 1)	(see Note 2)	(see Note 3)
Bonding Strength	Class 1 and Class 2	EN314-1/2:1993
Minimum Density	490kg/m <sup>3</sup>	EN323:1993
Release of Formaldehyde	Class E1	EN 13986 Annex B
Reaction to Fire	Class D-s2.D0 (Based on the density above)	EN 13986 Table 8
Water Vapour Permeability	Based on the density above, declared Vapour Resistance Factor: Wet Cup=50 μ . Dry Cup=150 μ	EN 13986 Table 9
Thermal Conductivity	0.13 W/m K	EN 13986 Table 11

Essential characteristics		Declared Performance		Technical Specification						
Bending Properties	Type	See below per Type		EN310:1993						
		5.5mm	8mm	9mm	10mm	12mm	15mm	18mm	22mm	25mm
Bending Strength	FK <sub>0</sub>	F10	F15	F15	F25	F25	F25	F25	F25	F25
	FK <sub>90</sub>	F10	F10	F20	F20	F25	F20	F20	F25	F25
Bending Stiffness MOE	Em <sub>0</sub>	E10	E15	E25	E35	E35	E30	E30	E30	E35
	Em <sub>90</sub>	E15	E15	E25	E30	E35	E30	E30	E30	E35

Where pursuant to Article 37 or 38 the specific Technical Documentation has been used, the requirements with which the product complies:

N/A

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Li Zhian/ Manager

(name and function)

Pizhou, China-5nd, Jan 2017

(place and date of issue)

(signature)