

Declaration of Performance
for product Plywood 2500X1220X3.6mm s.e
DoP-LY-009-CE-3.6

| | | |
|---|---|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 41 |
| | perpendicular (N/mm ²) | 29 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5587 |
| | perpendicular (N/mm ²) | 4105 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (molsture resistance) | 1.12 |
| | Moisture Content (Up to 14) (%) | 11.3 |
| | Density | 605 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products)is in conformity with the declared performance

This declaration of performance is issued the sole responsibility of the manufacturer, identified above.

Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager
(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X5mm s. e
DoP-LY-010-CE-5

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: Certificate N | SKH 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 42 |
| | perpendicular (N/mm ²) | 27 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5418 |
| | perpendicular (N/mm ²) | 4287 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.14 |
| | Moisture Content (Up to 14) (%) | 12.6 |
| | Density | 602 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager
(name and function)

Hegou Town Mar 14th, 2014
(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X5.5mm s. e
DoP-LY-011-CE-5.5

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified body: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 44 |
| | perpendiculare (N/mm ²) | 28 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5372 |
| | perpendiculare (N/mm ²) | 4215 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.23 |
| | Moisture Content (Up to 14) (%) | 12.1 |
| | Density | 600 |
| | Release of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager
(name and function)

Hegou Town Mar 14th, 2014
(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X8mm s.e
DoP-LY-012-CE-8

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|--------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 46 |
| | perpendicular (N/mm ²) | 41 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5391 |
| | perpendicular (N/mm ²) | 4552 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.18 |
| | Moisture Content (Up to 14) (%) | 11.5 |
| | Density | 595 |
| | Release of Formaldehyde | E1 |
| | Reaction to fire | Declared: D-s2, d0 |

The performance of the product (products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager

(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X9mm s.e
DoP-LY-013-CE-9

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 45 |
| | perpendiculare (N/mm ²) | 39 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5456 |
| | perpendiculare (N/mm ²) | 4527 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.14 |
| | Moisture Content (Up to 14) (%) | 12.5 |
| | Density | 590 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager

(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X10mm s.e
DoP-LY-014-CE-10

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 45 |
| | perpendiculare (N/mm ²) | 40 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5184 |
| | perpendiculare (N/mm ²) | 4210 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.21 |
| | Moisture Content (Up to 14) (%) | 12.9 |
| | Density | 585 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager

(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X12mm s.e
DoP-LY-015-CE-12

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified body: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 55 |
| | perpendiculare (N/mm ²) | 42 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5409 |
| | perpendiculare (N/mm ²) | 4687 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.32 |
| | Moisture Content (Up to 14) (%) | 12.8 |
| | Density | 580 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager

(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X15mm s. e
DoP-LY-016-CE-15

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| 8 Declared performance | | |
|--|--------------------|---|
| Essential characteristics | Performance | Harmonized technical specification |
| Bending strength parallel (N/mm ²) | 51 | ITT According to EN 310 |
| perpendicular (N/mm ²) | 42 | |
| Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5580 | ITT (EN314-1/2) |
| perpendicular (N/mm ²) | 4724 | |
| Classification according to EN636 | F20/15 E40/25 | EN636 |
| Bonding quality | Class 2 | ITT (EN314-1/2) |
| Durability (moisture resistance) (N/mm ²) | 1.32 | EN314-1/2 Section 6.6.5 |
| Moisture Content (Up to 14) (%) | 12.1 | EN 322 |
| Density | 575 | EN 323 |
| Release of Formaldehyde | E1 | EN 13986 Annex B, Note 2 (Use of Phenolic-Glue) |
| Reaction to fire | Declared: D-s2, d0 | |

The performance of the product (products) is in conformity with the declared performance.
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufacturer by:
Zhangaijun Quality Control Manager
(name and function)
Hegou Town Mar 14th, 2014
(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X18mm s. e
DoP-LY-017-CE-18

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|--------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 46 |
| | perpendicular (N/mm ²) | 41 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5540 |
| | perpendicular (N/mm ²) | 4821 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.16 |
| | Moisture Content (Up to 14) (%) | 12.6 |
| | Density | 570 |
| | Release of Formaldehyde | E1 |
| | Reaction to fire | Declared: D-s2, d0 |

The performance of the product (products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:
Zhangaijun Quality Control Manager
(name and function)
Hegou Town Mar 14th, 2014
(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X22mm s. e
DoP-LY-018-CE-22

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified body: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 51 |
| | perpendiculare (N/mm ²) | 42 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5561 |
| | perpendiculare (N/mm ²) | 4582 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.18 |
| | Moisture Content (Up to 14) (%) | 12.2 |
| | Density | 568 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products) is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager
(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)



Declaration of Performance
for product Plywood 2500X1220X25mm s.e
DoP-LY-019-CE-25

| | | |
|---|--|---|
| 1 | Identification code : | ALTRIPLY 250X122 Plywood, euca combi core, b/bb fsc Lotofa f/b, ce2+ exterior glue E1 (EN717-2) |
| 2 | Batch-/Serial number | |
| 3 | Intendent use: | Internal use as structural components in Humid condition |
| 4 | Harmonized technical specification | EN 13986:2004 |
| 5 | Manufacturer: | |
| 6 | System of Assessment and verification of constancy of performance (AVCP) | 2+ |
| 7 | Notified boby: | SKH |
| | Certificate N | 0502-CPR-10029 |

| | | |
|---|--|-------------------|
| 8 | Declared performance | |
| | Essential characteristics | Performance |
| | Bending strength parallel (N/mm ²) | 49 |
| | perpendicular (N/mm ²) | 38 |
| | Bending stiffness (Modulus Elasticity) parallel (N/mm ²) | 5640 |
| | perpendicular (N/mm ²) | 4652 |
| | Classification according to EN636 | F20/15 E40/25 |
| | Bonding quality | Class 2 |
| | Durability (moisture resistance) (N/mm ²) | 1.21 |
| | Moisture Content (Up to 14) (%) | 11.5 |
| | Density | 565 |
| | Realease of Formaldehyde | E1 |
| | Reaction to fire | Declared:D-s2, d0 |

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer, identified above.
Signed for and behalf of the manufactured by:

Zhangaijun Quality Control Manager
(name and function)

Hegou Town Mar 14th, 2014

(place and date of issue)

